Allied Telesis®

AT-SPFX/2

Small Form Pluggable (SFP) Modules

AT-SPFX/2
2km, 100FX, SFP

Industry Standard
The AT-SPF series offers the latest industry standard in flexible, full-duplex Fast Ethernet connectivity. These hot-swappable, fiber interfaces simply plug into a SFP slot on Allied Telesis SFP compatible products. Configurations can be optimized to meet varied distance and service requirements.

Options
The AT-SPF series offers short-haul and long-haul solutions. From the inexpensive AT-SPFX/2 to the long-haul AT-SPFX/40, you have the option to extend your network to the distances that meet your performance needs.

Product Compatibility
The AT-SPF series SFPs are compatible with all the Allied Telesis range of products that support 100Mbps SFP uplink connections.

Technical Specifications

Media Type	MMF
Wavelength	1310nm
Distance	2km
Digital Diagnostics	No
Transmit Power (min)	-20dBm
Transmit Power (max)	-14dBm
Receive Sensitivity (typ)	-29dBm
Power Budget (min)	9dBm
Fiber Connectors	LC

Standard Data Rates Supported
Optical Fast Ethernet

Environmental Specifications

Operating Temp	-40°C to 85°C
Operating Humidity	0% to 85% (non-condensing)
Storage Temperature	-40°C to 85°C
Storage Humidity	0% to 80% (non-condensing)

Key Features

- Connect up to 2km
- Compact size
- Flexible architecture
- Plug & Play ease-of-use
- Self-locking mechanism
- Two year warranty

Ordering Information

AT-SPFX/2
2km, 100FX (LC), 1310nm

Connecting The (IP) World

Allied Telesis®