

Product Highlights

High-speed Transmission


High-speed data transmission at rates of up to 40 Gbps allow for seamless data transfer¹

Advanced Features

802.3x flow control for traffic management, 802.1Q VLAN tagging for increased security, and checksum offloading to reduce CPU processing burden

Bandwidth Management

NIC partitioning enables administrators to manage bandwidth for greater network efficiency



DXE-820T

Dual Port 10 Gigabit Ethernet PCIe Adapter

Features

High-Performance:

- PCI Express Interface v2.0
- Auto-negotiation
- Up to 40 Gbps throughput

Advanced Standards-based Enterprise Features:

- 802.1Q VLAN tagging
- 802.3x flow control
- 802.3ad teaming
- Jumbo frame support
- SNMP statistics
- TCP/UDP/IP checksum offloading

Add 10 Gigabit connectivity to your server or high-powered workstation with the D-Link DXE-820T Dual Port 10 Gigabit Ethernet PCIe Adapter. It is a high performance network adapter which combines 10GBase-T with high-speed PCI Express 2.0 x8 interface. The DXE-820T offers increased bandwidth over standard Cat 6a cabling without the need to overhaul your infrastructure wiring or invest in a costly upgrade to fibre. Furthermore, the PCI express interface offers increased bandwidth, reliability and functionality compared with standard PCI network cards. It is specifically designed to allow throughput at rates up to 40 Gbps, thus eliminating the bottleneck that exists with current 32 and 64-bit PCI bus architectures.

Advanced Features and Security

The adapter features onboard screening of 802.1Q VLAN tagged Ethernet frames, allowing you to assign multiple subnets to each server and isolate devices within each VLAN from the rest of the network for better traffic control and security. With support for advanced features such as 802.3x flow control, jumbo frames, and SNMP for network management, the DXE-820T can easily interoperate with your current networking equipment.

Performance and Reliability

The DXE-820T increases network throughput by utilising PCI Express bus architecture. With Smart Load Balancing™, the DXE-820T configures multiple adapters to work as a team, sharing traffic and ensuring data reliability. This creates both a faster network and provides fault tolerance resulting in a stable and efficient network.

Checksum Offloading

The DXE-820T features TCP, UDP, and IP checksum offloading functionality, which transfers the checksum processing tasks from the computer's CPU to the network card. The DXE-820T's ability to handle the checksum processing means that the CPU's processing power can be used for other tasks while still achieving 20 Gbps network speeds.

DXE-820T Dual Port 10 Gigabit Ethernet PCIe Adapter

Technical Specifications

General

Standards	<ul style="list-style-type: none"> • IEEE 802.1Q VLAN tagging • IEEE 802.3x flow control • IEEE 802.3an 10GBASE-T • IEEE 802.3ab 1000BASE-T 	<ul style="list-style-type: none"> • IEEE 802.3u 100BASE-TX • IEEE 802.3az Energy-Efficient Ethernet (EEE) • IEEE 802.3ad teaming • PCI Express x8 2.0, 5 GT/s compliant
Power	<ul style="list-style-type: none"> • Maximum Power Consumption: 23.38 W 	<ul style="list-style-type: none"> • Input Voltage: 3.3 V and 12 V
Data Transfer Rate	<ul style="list-style-type: none"> • 1 Gbps Full Duplex • 10 Gbps Full Duplex 	<ul style="list-style-type: none"> • Auto mode (support 100 Mbps)
Transmit Distance	<ul style="list-style-type: none"> • 10GBASE-T <ul style="list-style-type: none"> • 100M with Cat 6A or higher UTP • 50M with Cat 6 UTP 	<ul style="list-style-type: none"> • 100/1000BASE-T <ul style="list-style-type: none"> • 100M with Cat 5 or higher UTP
Interface Slot	<ul style="list-style-type: none"> • PCI Express v2.0 x8/x16 slot 	
Supported Functions	<ul style="list-style-type: none"> • NIC partitioning • Other performance features <ul style="list-style-type: none"> • TCP, IP, UDP checksum • TCP segmentation • Adaptive interrupts • Receive Side Scaling (RSS) • Manageability <ul style="list-style-type: none"> • Statistics for SNMP MIB II, Ethernet-like MIB, and Ethernet MIB • SMBus controller • IPMI support (IPMI pass thru mode) • Advanced network features <ul style="list-style-type: none"> • Jumbo frames (up to 9 KB) • Virtual LANs • Smart load balancing teaming • LiveLink™ (supported in both the 32-bit and 64-bit Windows operating systems) 	<ul style="list-style-type: none"> • Logical Link Control (IEEE Std 802.2) • Layer-2 Priority Encoding (IEEE Std 802.1p) • High-speed on-chip RISC processor • Up to 3 classes of service (CoS) • Integrated 96 KB frame buffer memory • Quality of Service (QoS) • Support for multicast addresses via 256 bits hashing hardware function • JTAG support • PCI Power Management Interface (v1.1) • 64-bit BAR support • iSCSI Boot support • Virtualization <ul style="list-style-type: none"> • Microsoft • VMware
Functionality		
Driver Support	<ul style="list-style-type: none"> • Windows Server 2008 (x86, x64)/2008 R2 (x64) • Windows Server 2012 • RHEL 6.4/6.5 (x64), RHEL 5.9 (x64) 	<ul style="list-style-type: none"> • SLES 11.2/11.3 (x64) • Solaris 11/11.1
Diagnostic LED	<ul style="list-style-type: none"> • Speed/Link 	<ul style="list-style-type: none"> • Activity
Physical		
Dimensions	<ul style="list-style-type: none"> • 181 mm x 120.9 mm x 21.6 mm (7.13 x 4.76 x 0.85 inches) 	
Temperature	<ul style="list-style-type: none"> • Operating: 0 to 40 °C (32 to 104 °F) 	<ul style="list-style-type: none"> • Storage: -20 to 70 °C (-4 to 158 °F)
Humidity	<ul style="list-style-type: none"> • Operating: 10% to 90% non-condensing 	<ul style="list-style-type: none"> • Storage: 10% to 90% non-condensing
Certifications	<ul style="list-style-type: none"> • CE • FCC 	<ul style="list-style-type: none"> • C-Tick

¹ When connected in full-duplex mode.



For more information: www.dlink.com

D-Link European Headquarters. D-Link (Europe) Ltd., D-Link House, Abbey Road, Park Royal, London, NW10 7BX. Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners. ©2015 D-Link Corporation. All rights reserved. E&OE.

Updated October 2015

D-Link®
Building Networks for People