**2 Port USB VGA Cable KVM Switch with Audio**

*StarTech ID: SV215MICUSBA*



The SV215MICUSBA 2 Port USB VGA Cable KVM Switch with Audio offers a high resolution (up to 2048x1536) solution for accessing and controlling two desktop computers from a single KVM (Keyboard, Video, Mouse) peripheral set.

A complete solution, this cable-style KVM switch includes all of the cables and connections required to share one monitor, keyboard and mouse, as well as speakers, across two computers. Plus, the switch features independent audio/microphone switching to ensure an uninterrupted audio experience, even when switching between computers.

Compatible with Mac, Linux or PC based computers the SV215MICUSBA is the perfect addition for a broad range of environments, and because of its space-saving "KVM-on-a-cable" design, no desk space is required for installation – an ideal choice for most environments, including SOHO (small or home offices), gaming, multimedia production workstations and more.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

 **Applications**

- Ideal for desktops, workstations and servers that require full multi-media support
- Ideal for graphic designers, engineers, multi-media designers, and industries using CAD/CAM applications, where high resolution display units are required
- Sharing computers and attached peripherals in the home/SOHO/multimedia environment

**Features**

- Complete micro design saves space and money
- Compatible with all USB supported Operating Systems
- Designed for high-resolution applications: 2048x1536 analog resolution with DDC2B
- Computer selection by Remote selector and keyboard hotkeys
- Hot Pluggable - add or remove computers without having to power down the computers
- LED indicators for easy status monitoring
- USB 2.0/1.1 specification compliant

**Technical Specifications**

| | |
|---|---|
| Warranty | 2 Years |
| Audio | Yes |
| KVM Ports | 2 |
| PC Interface | USB |
| PC Video Type | VGA |
| Multi-Monitor | No |
| Rack-Mountable | No |
| Cables Included | Yes |
| Daisy-Chain | No |
| Console Interface(s) | 2 - VGA (15 pin; High Density D-Sub) Male |
| Console Interface(s) | 4 - 3.5 mm Mini-Jack (3 Position) Male |
| Console Interface(s) | 4 - USB A (4 pin) Male |
| Host Connectors | 1 - VGA (15 pin; High Density D-Sub) Female |
| Host Connectors | 2 - 3.5 mm Mini-Jack (3 Position) Female |
| Host Connectors | 2 - USB A (4 pin) Female |
| DVI Support | No |
| IP Control | No |
| Maximum Analog Resolutions | 2048x1536 |
| Maximum Number of Users | 1 |
| Port Selection Support | Push Button and Hotkeys |
| OS Compatibility | OS independent; No software or drivers required |
| **Note** | One host cable is 47 inches long, the other is 24 inches. Remote selector cable is 70 inches long |
| Color | Black |
| Enclosure Type | Plastic |
| Product Length | 31.9 in [810 mm] |
| Product Width | 27.2 in [690 mm] |
| Product Height | 10.2 in [260 mm] |
| Product Weight | 14.1 oz [400 g] |
| Shipping (Package) Weight | 1.2 lb [0.6 kg] |
| Included in Package | 1 - 2 Port Integrated KVM |
| Included in Package | 1 - Remote Selector |

**Certifications, Reports and Compatibility**

$CE$

$CE$

FC

OperatingSystem
Independent

RoHS Compliant
Available