

Nuclias Connect Device Compatibility*

Nuclias Connect Supported Wireless Access Points					
Model	DAP-2660	DAP-2662	DAP-2680	DAP-2682	DAP-2695
Environment	Indoor	Indoor	Indoor	Indoor	Indoor
Product Image					
H/W Version	Ax	Ax	Ax	Ax	Ax
IEEE Standard	802.11a/b/g/n/ac	802.11a/b/g/n/ac	802.11a/b/g/n/ac	802.11a/b/g/n/ac	802.11a/b/g/n/ac
2.4 GHz Speed	300 Mbps	300 Mbps	450 Mbps	600 Mbps	450 Mbps
5 GHz Speed	867 Mbps	867 Mbps	1300 Mbps	1732 Mbps	1300 Mbps
Number of SSIDs	16 (8 per radio)	16 (8 per radio)	16 (8 per radio)	16 (8 per radio)	16 (8 per radio)
Ethernet Interface	1 x Gigabit Ethernet	1 x Gigabit Ethernet	1 x Gigabit Ethernet	2 x Gigabit Ethernet	2 x Gigabit Ethernet
PoE	802.3af	802.3af	802.3at	802.3at	802.3at
Max Tx Power	2.4 GHz: 26 dBm 5 GHz: 26 dBm	2.4 GHz: 26 dBm 5 GHz: 26 dBm	2.4 GHz: 26.5 dBm 5 GHz: 26.5 dBm	2.4 GHz: 23 dBm 5 GHz: 23 dBm	2.4 GHz: 27.5 dBm 5 GHz: 27.5 dBm
Antenna Type	Internal	Internal	Internal	Internal	External
Antenna Gain	2.4 GHz: 3 dBi 5 GHz: 4 dBi	2.4 GHz: 3.8 dBi 5 GHz: 3.8 dBi	2.4 GHz: 3.6dBi 5 GHz: 4.2 dBi	2.4 GHz: 2 dBi 5 GHz: 2 dBi	2.4 GHz: 4 dBi 5 GHz: 6 dBi
Mounting Type	Ceiling/Wall/Desktop	Ceiling/Wall/Desktop	Ceiling/Wall/Desktop	Ceiling/Wall/Desktop	Wall/Desktop
Security Lock	Yes	Yes	Yes	Yes	Yes

* Please contact your local D-Link office for availability.