



External Transparent Permanent End Caps

Direct Buried / Push Fit

General Data

Item	End Cap
Description	A transparent end cap which can be direct buried and is suitable for use with a wide range of ducts providing protection against gas and water ingress up to 5 bar. The HellermannTyton range of end caps are fitted with a locking ring which is quick and simple to fit.

Product Specification

Material	Polycarbonate PC				
Part Code		Diameter	Length	Unit	Pack Size
Dimensions	EC-5MM-EXT	16.8	19.5	mm	100
	EC-7MM-EXT	18.8	21.5		
	EC-8MM-EXT	18.8	21.5		
	EC-10MM-EXT	22.2	25.1		
	EC-12MM-EXT	25.0	26.3		
	EC-14MM-EXT	26.7	27.0		
	EC-16MM-EXT	29.2	29.9		
	EC-18MM-EXT	32.0	31.5		
	EC-20MM-EXT	34.0	33.0		
	EC-25MM-EXT	41.2	37.5		50
Pressure	0.5 (permanent gas and watertight)			Bar	
	15 / 30			Bar / Min	
Burst Pressure	Min. 30			Bar	
Tensile Strength	EC-5MM-EXT	Min. 120		N	
	EC-7MM-EXT	Min. 300			
	EC-8MM-EXT	Min. 300			
	EC-10MM-EXT	Min. 400			
	EC-12MM-EXT	Min. 450			
	EC-14MM-EXT	Min. 500			
	EC-16MM-EXT	Min. 600			
	EC-18MM-EXT	Min. 600			
	EC-20MM-EXT	Min. 600			
	EC-25MM-EXT	Min. 800			