

Reducer

The Reducer allows interconnection between microducts that are different in outer diameters. Usually, this is used in the point of transition from DB to DI microducts entering the office, house.

Product Specifications	
Material	Clear PC
Leakage Pressure	15 bar
Negative Pressure	750mm Hg(10 Torr)
Proof Pressure	25 bar
Temperature Range	-10 - 60 °C
Burst Pressure	>25.5kgf/cm ²
Water Immersion Test	Pass (Waterproof)
Expected Life Time	Minimum 20 years
Hydraulic Pressure Test	Pass (Resisting at 13.5kgf/cm ² for 2 minutes)



Size (mm)		Product Codes
5.3.5	3/2.1	RR53AU
5/2.1	4/2.1	RR54AU
7/4	4/2.1	RR74AU
7/3.5	5/3.5	RR75BU
8/4.4	5/3.5	RR85AU
8/5.5	5/3.5	RR85BU
10/8	8/6	RR10EU
10/8	8/5.5	RR10FU
10/6	8/6	RR10GU
10/5.5	7/5.5	RR10CU
10/8	7/3.5	RR10DU
12/8	10/6	RR12FU
12/8	10/8	RR12GU
12/10	10/8	RR12HU
12/10	7/3.5	RR12BU
12/10	7/5.5	RR12CU
14/10	12/8	RR14FU
14/10	12/10	RR14HU
14/12	12/10	RR14GU
16/12	14/10	RR16DU
16/12	12/10	RR16BU
16/12	12/8	RR16CU