

# TriggAir Fiber Blowing Machine

TriggAir is a robust handheld battery powered fiber blowing tool optimized for FTTx installation of blown fiber (EPFU) and micro/nano cables, from 0.8 to 3mm into duct size 3, 5, 7 and 8mm. The effective fiber security, and adjustable clamping force ensures that all cable designs can be installed effective and safe. Delivered in a strong transport case with batteries, charger and an assortment of cable seals.

## Features & Benefits

- Electrically operated & battery connected
- Fiber security by mechanical clutch & adjustable clamping force
- Forward and reverse
- Drive wheel with rubber rings secure a good & soft grip
- Digital display showing speed & distance
- Max speed: 150m/min
- Max pushing force: 30N
- Speed control with constant speed support



## Standard TriggAir Kit Contains

- Transport case
- TriggAir machine
- 110/230 Charger for 12V battery
- 2 pcs 12V lithium battery with 4Ah Milwaukee connector
- Cable Seal assortment:
  - 10 pcs 1.2mm
  - 10 pcs 1.8mm
  - 10 pcs 2.2mm
  - 10 pcs 2.8mm
- Original Jetting Duct cutter
- User manual
- Seal for duct clamp



Product Specifications		
Case Dimensions (W x H x D)	460 x 350 x 180mm / 18.1 x 13.8 x 7.1in	
Weight	TriggAir Fiber Blowing Machine	Approx 2.3kg/14lbs (with battery)
	Including Transport Case	Approx 6.3kg/13lbs
Cable Diameter	0.8-3mm	
Duct Diameter	3, 5, 7 & 8mm	
Max Speed	150m/min 492ft/min	
Pushing Force	Up to 30N/ 6.7lbf	
Battery	12V, 4Ah Milwaukee	
Max Pressure	16 Bar/ 232psi	
Air Connection	Std 3/8" Cejn	

# TriggAir Fiber Blowing Machine

Ordering Information	
Product Description	Part Number
TriggAir Fiber Blowing Machine	TriggAIR-CAN
Foldable Tripod	660432
Reel Arm Kit For Pre-Terminated Mini Drums	17011
Reel Arm Spacer Kit	17013
Drive Wheel U-Groove For 2-3mm Cable	17015
TriggAir Table Bracket (with US Air Connections)	17016-USA
Set of O-ring for TriggAir (Drive wheel)	34039
TriggAir 3mm Duct Adaptor	17017
TriggAir Extended Warranty	66071