

12 Fibre Internal/External Break Out Box

This lockable IP65 distribution box offers the ability to terminate 12 fibres housed in a robust ABS enclosure for indoor and outdoor applications.

With the ability to use a full array of adaptor types offering a flexible solution to the end user, enabling them to incorporate a multi-functional enclosure which allows easy access during installation or re-work with no disturbance of the existing cable or fibres.

In addition to the array of adaptors the enclosure also offers up to 12 exit points for patching cables and a standard cable entry point for loose tube, tight buffer, pre-terminated and steel tape armoured cable. Each enclosure has integrated strength member tie positions and bend radius protection with the addition of a removable front door allowing for quick and easy installation.

Features & Benefits

- Up to 12 fibres
- Removable splice tray for easy installation
- Multiple adaptor options available
- 6 adaptor positions
- Accepts loose tube, distribution and pre-terminated cables
- Integrated bend radius protection
- Sealing glands for up to 12 cables
- Removable door for ease of installation
- Supplied with 12 heat shrink splice protectors
- Supplied with transit tubing
- Supplied with wall fixings and tie wraps

Applications

- Data centres, premise installations, telecommunication networks
- Ethernet, Fibre Channel, ATM, LAN, MAN and WAN
- Data communication and telecommunication networks
- Indoor applications



Product Specifications	
Height (mm)	258
Width (mm)	186
Depth (mm)	61
Net Weight (g)	850
Packaged Dimensions (W x H x D) (mm)	197 x 275 x 65
Packed Weight (g)	875
IP Rating	IP65S
Suitable for Adaptor Type	SC Duplex, LC Quad
Number of Fibres	12
Number of Ports	6
Cable Entry	20mm x 1
Cable Exit	20mm x 2
Material	ABS
Designed in Accordance With	ANSI/TIA, 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754, EN297-1



Ordering Information	
Product Description	Part Number
12 Fibre Internal/External Break Out Box	009-008-000-15