



5-Port Gigabit PoE+ Switch TPE-TG50g (v1.0R)

- 4 x Gigabit PoE+ ports and 1 x Gigabit port
- 31 Watts PoE budget
- 10 Gbps switching capacity
- Sturdy metal switch
- Plug and Play installation
- Use with TRENDnet's PoE Splitter to network and power non-PoE devices

The 5-Port Gigabit PoE+ Switch, model TPE-TG50g, delivers data and power over existing Ethernet cables to Power over Ethernet (PoE) devices such as Access Points and IP Cameras. It supports both PoE (802.3af) and PoE+ (802.3at) devices with a 31 Watts PoE budget. Plug and Play this sturdy metal switch for reliable high speed PoE networking.

Hardware



PoE+

Supplies up to 30 Watts of PoE power per port with a 31 Watts PoE budget



Ports

4 x Gigabit PoE+ ports and 1 x Gigabit port



Switching Capacity

10 Gbps switching capacity




Jumbo Frame

Sends larger packets, or Jumbo Frames (up to 9 KB) for increased performance



Energy Savings

Embedded GREENnet technology reduces power consumption by up to 70%*



Housing

Rugged metal enclosure



LED Indicators

LED indicators convey port status

Networking Solution



① Power

② Gigabit PoE+ ports

③ Gigabit port

Specifications

Standards

- IEEE 802.3
- IEEE 802.3u
- IEEE 802.3x
- IEEE 802.3ab
- IEEE 802.3af (15.4 Watts/port)
- IEEE 802.3at (30 Watts/port)
- IEEE 802.3az

Device Interface

- 4 x Gigabit PoE/PoE+ ports
- 1 x Gigabit port
- LED indicators

Data Transfer Rate

- Ethernet: 10 Mbps (half duplex), 20 Mbps (full duplex)
- Fast Ethernet: 100 Mbps (half duplex), 200 Mbps (full duplex)
- Gigabit: 2000 Mbps (full duplex)

Performance

- Data RAM Buffer: 96 KB
- Switch Fabric: 10 Gbps
- MAC Address Table: 1 K entries
- Forwarding rate: 7.44 Mpps (64-byte packet size)
- Jumbo Frame: 9 K

Special Features

- GREENnet energy saving technology

Power

- Input: 110-240 V AC, 50/60 Hz, 0.75 A
- Output: 48 V DC, 0.75 A
- Consumption: 36 Watts (Max.)

PoE

- PoE budget: 31 Watts
- Pin 3,6 for power+ and pin 1,2 for power- (mode A)

Operating Temperature

- 0 – 40 °C (32 - 104 °F)

Operating Humidity

- Max. 90% non-condensing

Dimensions

- 141 x 95 x 30 mm (5.6 x 3.7 x 1.2 in.)

Weight

- 370 g (13 oz.)

Certifications

- CE
- FCC

Warranty

- 3 year limited

Package Contents

- TPE-TG50g
- Quick Installation Guide
- Power adapter

