


# BX500CI

400-1500VA



Peace of mind from the world's most trusted UPS.

## PRODUCT FEATURES

- Back up and protect your hardware and data during power outages, surges and spikes.
- Protect secondary electronics from surges and spikes without reducing battery power used to run primary electronics during an outage.
- Periodic battery self-test ensures early detection of a battery that needs to be replaced.
- Provides early-warning fault analysis on batteries enabling timely preventive maintenance
- Maximizes battery performance, life, and reliability through intelligent, precision charging.
- Easy recovery from overloads; no need to replace a fuse.
- Provides notification of changing utility power and UPS power conditions
- Quickly understand unit and power status with visual indicators.
- Ensures the product has been tested and approved to work safely with the connected service provider
- Reserves power capacity and run time for connected equipment that require UPS battery back-up while providing surge only protection for less critical equipment
- Provides protection of connected equipment from power surges on the data lines.
- Provides peace of mind by providing professional data recovery services in the event data is lost due to the failure of the unit.
- Easy recovery from overloads; no need to replace a fuse.

# Technical Specifications

BX500CI	
<b>Output</b>	
Output Power Capacity	300 Watts / 500 VA
Max Configurable Power	300 Watts / 500 VA
Nominal Output Voltage	230V VA
Output Frequency (sync to mains)	50 Hz
Topology	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Output Connections	(3)IEC 320 C13(Battery Backup) (1)IEC Jumpers(Battery Backup)
<b>Input</b>	
Nominal Input Voltage	230V
Input Frequency	45 - 65 Hz
Input Connections	IEC-320 C14(Battery Backup)
Cord Length	6 feet(1.83 meters)
Input voltage range for main operations	160 - 280V
Maximum Input Current	2
<b>Batteries &amp; Runtime</b>	
Replacement Battery	APCRBC114
<b>Communications &amp; Management</b>	
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
<b>Surge Protection and Filtering</b>	
Surge energy rating	273 Joules
<b>Physical</b>	
Maximum Height	7.30 inches(185 mm)
Maximum Width	4.53 inches(115 mm)
Maximum Depth	8.39 inches(213 mm)
Net Weight	11.44 lbs.(5.20 kg)
Shipping Weight	12.50 lbs.(5.68 kg)
Shipping Height	10.12 inches(257 mm)
Shipping Width	7.48 inches(190 mm)
Shipping Depth	11.46 inches(291 mm)
Master Carton Units	2.00
Color	Black
SCC Codes	6073130430736 7
Units per Pallet	60.00
<b>Environmental</b>	
Operating Environment	32 - 104(0 - 40 &deg;C)
Operating Relative Humidity	0 - 95
Operating Elevation	0-10000 feet(0-3000 meters)
Storage Temperature	5 - 113 meters(-15 - 45 &deg;C)
Storage Relative Humidity	0 - 95
Storage Elevation	0-50000 feet(0-15000 meters)
Audible noise at 1 meter from surface of unit	45.00 dBA
<b>Conformance</b>	
Regulatory Approvals	CE
Standard Warranty	2 years repair or replace
<b>Sustainable Offer Status</b>	
REACH	REACH: Contains No SVHCs
PEP	Available in Documentation tab
EOLI	Available in Documentation tab
Battery Directive	Compliant
Other Environmental Compliance	China RoHS